



Project Name:	
Item Number:	
Quantity:	
Length:	



CHOICE™ Support:

☐ 1" OD Stainless Steel Contact factory for additional tubing options

NSF Listed Finishes:

_	Diusileu	("")
	Polished	(#8)

Stainless

Ц	Fla	at E	3la	Ck

☐ Wrinkle Black

1	Unlimited	Powder	Coats,	specify

RAL#: __ or PMS#:

Glass:

☐ 1/4" Glass - 48" max. Span

☐ 3/8" Glass - 60" max. Span

Contact factory for spans exceeding max.

End Panels:


☐ Both (Std.)


■ Right Only

■ None

■ Left Only

As required by current NSF / ANSI 2 standards, all food shields will be quoted with side end panels unless customer requests otherwise. Standards available upon request.





Advise Counter Thickness and Material

Mounting Options:
Some mounting options may not be available on some cantilevered/counter substrate combinations. Refer to mounting cut-sheet or contact factory for additional information.

4 641-1

Above Counter Surface Mount

☐ 640B-2/1

Above Counter Surface Mount with Stainless Flange

☐ 644B-3/1

Narrow Above Counter Surface Mount with Stainless

Flange Cover

223

Through Counter Mount (Standard when rear legs

are not possible)

☐ Other:

Electrical Components:

Lights Only

- ☐ Ultra-Slim[™] Fluorescent 4100CCT * (Std.)
- ☐ Ultra-Slim[™] LED Display Light (ideal over refrigerated product areas)

Heat Strip Only

☐ Hatco GRNM Narrow Heat Strip (Std.) (Other Hatco heat strips available)

Heat / Light Combo

☐ Hatco GRNM Narrow Heat Strip and Ultra-Slim[™] Fluorescent 4100CCT * (Std.) (Other Hatco heat/combo units available)

Please see electrical cut sheet for additional options and wiring diagram.

Specifications for reference only and may be changed without notice. All orders require approved shop drawings prior to release to production. Products are drawn & built to meet NSF Standard 2. It is the responsibility of the customer to ensure product meets local health board standards.

Web: www.pmg-inc.com Email: info@pmg-inc.com Phone: 1-800-251-5800 1-800-251-2515 Fax:





